



Micropak

IP44-IK08

Class 2

Patented design



The tiny wall-mounted or console junction box, discreet and attractive. It can also be used on lampposts and other posts.

Micropak can connect up to 2 x 3G2.5 mm² cables (Ø 12 mm).

Two possible cable inputs:
via the bottom or back of the box.

Closure by clipping flap on the cover.

Captive cable clamp for front insertion of cables.

Option: Micropak sound system with shielded cable (length as per customer specifications) and 3-pole XLR plug.

ADVANTAGES

Very compact and discreet.

Easily opened with a screwdriver.

TECHNICAL CHARACTERISTICS

Max. capacity

- 1 FPN + 6 mm² earth, or 3 BD2 terminals.
- Up to 2 x Ø 12 mm cables (3G2.5 mm²), via the bottom of the box.
- Up to 2 x Ø 10 mm cables, via the back of the box, with optional weatherproof grommets.

Mounting

- With lugs, for attachment by 20 mm strap (MCP).

Casing

- Polypropylene copolymer, self-extinguishing, UV treated.
- IP44 in accordance with IEC 60529 (open junction box: IP2X).
- IK08 in accordance with EN 62262.
- Class 2 (can also be supplied with insulated earth terminal).
- -40°C to +130°C.

Product standards

- EN 60439-1.

Installation standards

- NF C17-200.

Standard colours:

- MCP (with lugs)

